

SHD - pressure transmitter



Technical Data

Outputs	0...10V / 4...20mA
Supply	12...26 Vac / 14...30 Vdc
Process connection	G 1/4" optional G1/2" or NPT 1/2" (with adapter ADAP)
Measuring ranges	-1 ... 24 bar 0 ... 600 mbar 0 ... 100 bar
Accuracy	< +/- 0,5% @ 25°C (+/- 5°C)
Operating temperature	-40°C...+125°C
Membrane	Stainless steel

1. Output

Order code	Output signal	Price
SHD-U	0...10V	135,00 €
SHD-I	4...20mA	138,00 €

2. Measuring range

Order code	Measuring range	Surcharge
.-1/0	-1...0 bar	53,00 €
.-1/1,5	-1...1,5 bar	53,00 €
.-1/5	-1...5 bar	53,00 €

.0/160mb	0...160 mbar	56,00 €
.0/250mb	0...250 mbar	56,00 €
.0/600mb	0...600 mbar	56,00 €

.0/1	0...1 bar	-
.0/6	0...6 bar	-
.0/10	0...10 bar	-
.0/16	0...16 bar	-
.0/25	0...25 bar	-
.0/60	0...60 bar	-
.0/100	0...100 bar	-

Other measuring ranges on request

Ordering example

1.	SHD-I	SHD, Output 4-20mA
2.	.0/10	0...10 bar

Total order code	Price
SHD-I.0/10	138,00 €

Accessories

Order code	Description	Price
ADAP-G1/2	Adapter to G1/2"	12,50 €
ADAP-NPT1/2	Adapter to NPT1/2"	12,50 €